



MATERIAL SAFETY DATA SHEET

February 03, 2010

SECTION 1	CHEMICAL PRODUCT AND COMPANY IDENTIFICATION
------------------	--

Product Name: **Portland Cements (Types I, II, III, IV, V)**

Manufacturer's Name and Address:

Salt River Materials Group
Phoenix Cement Company
8800 E. Chaparral Rd. Suite 155
Scottsdale, AZ 85250-2606

24 – Hour Emergency Telephone: CHEMTREC: 1-800-424-9300

Customer Service: (480)-850-5757 Fax (480) 850-4333

Chemical Name: Mixture

Chemical Formula: Complex mixture of inorganic minerals including metals and silica

SECTION 2	COMPOSITION / INFORMATION ON INGREDIENTS
------------------	---

Ingredients:

Portland cement (CAS #65997-15-1) – approximately 94% by weight

ACGIH TLV-TWA (1995-1996) = 10 mg total dust/m³

OSHA PEL (8-hour TWA) = 50 million particles/ft³

Gypsum (CAS #7778-18-9) approximately 6% by weight

ACGIH TLV (1995-1996) = 10 mg total dust/m³

OSHA PEL (8-hour TWA) = 10 mg total dust/m³

OSHA PEL (8-hour TWA) = 5 mg respirable dust/m³

Respirable quartz (CAS #14808-60-7) less than 0.75% by weight

ACGIH TLV – TWA (1995-1996) = 0.10 mg respirable quartz dust/m³

OSHA PEL (8-hour TWA) = (10 mg of respirable dust/m³) / (percent silica + 2)

NIOSH REL (8-hour TWA) = 0.05 mg respirable quartz dust/m³

Portland Cements (Types I, II, III, IV, V)

Other ingredients

Diethylene-glycol (CAS #111-46-6) less than 0.1% by weight

Amine Phenolate (CAS #23184-71-6 / 64601-03-2) less than 0.1% by weight

Trace Constituents

Portland cement is made from materials mined from the earth and is processed using heat provided by fossil fuels. Trace amounts of naturally occurring; potentially harmful chemicals might be detected during chemical analysis. For example, Portland cement may contain up to 0.75% insoluble residue, some of which may be free crystalline silica. Other trace constituents may include calcium oxide (also known as lime or quick lime), magnesium oxide, potassium sulfate, sodium sulfate, chromium compounds, and nickel compounds.

SECTION 3	HAZARD IDENTIFICATION
------------------	------------------------------

Emergency Overview:

Portland cement is a light gray powder that poses little immediate hazard. A single short-term exposure to the dry powder is not likely to cause serious harm. However, exposure of sufficient duration to wet Portland cement can cause serious, potentially irreversible tissue (skin or eye) destruction in the form of chemical (caustic) burns. The same type of tissue destruction can occur if wet or moist areas of the body are exposed for sufficient duration to dry Portland cement.

POTENTIAL HEALTH EFFECTS

Relevant Routes of Exposure:

Eye contact, skin contact, inhalation, and ingestion.

Inhalation:

Portland cement may contain trace amounts of free crystalline silica. Prolonged exposure to respirable free crystalline silica can aggravate other lung conditions and cause silicosis, a disabling and potentially fatal lung disease. (Also see "Carcinogenic potential" below)

Exposure to portland cement may cause irritation to the moist mucous membranes of the nose, throat, and upper respiratory system. It may also leave unpleasant deposits in the nose.

Ingestion:

Although small quantities of dust are not known to be harmful, ill effects are possible if larger quantities are consumed. Portland cement should not be eaten.

Eyes:

Exposure to airborne dust may cause immediate or delayed irritation or inflammation.

Eye contact by larger amounts of dry powder or splashes of wet portland cement may cause effects ranging from moderate eye irritation to chemical burns and blindness. Such exposures require immediate first aid (see Section 4) and medical attention to prevent significant damage to the eye.

Portland Cements (Types I, II, III, IV, V)

Skin:

Discomfort or pain cannot be relied upon to alert a person to hazardous skin exposure. Consequently, the only effective means of avoiding skin injury or illness involves minimizing skin contact, particularly contact with wet cement. Exposed persons may not feel discomfort until hours after the exposure has ended and significant injury has occurred.

Exposure to dry portland cement may cause drying of the skin with consequent mild irritation or more significant effects attributable to aggravation of other conditions. Dry portland cement contacting wet skin or exposure to moist or wet portland cement may cause more severe skin effects including thickening, cracking or fissuring of the skin. Prolonged exposure can cause severe skin damage in the form of (alkali) chemical burns.

Carcinogenic potential:

Portland cement is not listed as a carcinogen by NTP, OSHA, or IARC. It may, however, contain trace amounts of substances listed as carcinogens by these organizations.

Crystalline silica, a potential trace level contaminant in portland cement, is now classified by IARC as a known human carcinogen (Group 1). NTP has characterized respirable silica as “reasonably anticipated to be [a] carcinogen”.

Medical conditions which may be aggravated by inhalation or dermal exposure:

Pre-existing upper respiratory and lung diseases.

Unusual (hyper) sensitivity to hexavalent chromium (chromium)⁺⁶ salts.

SECTION 4	FIRST AID MEASURES
------------------	---------------------------

Eyes:

Immediately flush eyes thoroughly with water. Continue flushing eye for at least 15 minutes, including under lids, to remove all particles. Call physician immediately.

Skin:

Wash skin with cool water and pH-neutral soap or a mild detergent. Seek medical treatment in all cases of prolonged exposure to wet cement, cement mixtures, liquids from fresh cement products, or prolonged wet skin exposure to dry cement.

Inhalation of Airborne Dust:

Remove to fresh air. Seek medical help if coughing and other symptoms do not subside. (“Inhalation” of gross amounts of portland cement requires immediate medical attention)

Ingestion:

Do not induce vomiting. If conscious, have the victim drink plenty of water and call physician immediately.

Portland Cements (Types I, II, III, IV, V)

SECTION 5	FIRE FIGHTING MEASURES
------------------	-------------------------------

Flash Point [provided method used]:

None

Upper Explosion Limit: None

Lower Explosion Limit: None

Auto ignition Temperature:

Not combustible

Extinguishing Media:

Not combustible

Special Fire Fighting Procedures:

None – (Although portland cement poses no fire-related hazards, a self-contained breathing apparatus is recommended to limit exposure to combustion products when fighting any fire.)

Hazardous Combustion Products:

None

Unusual Fire and Explosion Hazards:

None

SECTION 6	ACCIDENTIAL RELEASE MEASURES
------------------	-------------------------------------

Personal Precautions:

Collect dry material using a scoop. Avoid actions that cause dust to become airborne. Avoid inhalation of dust and contact with skin. Wear appropriate personal protective equipment as described in Section 8.

Environmental Precautions and Methods for Clean up:

Scrape up wet material and place in an appropriate container. Allow the material to “dry” before disposal. Do not attempt to wash Portland cement down drains.

Dispose of waste material according to local, state and federal regulations.

SECTION 7	HANDLING AND STORAGE
------------------	-----------------------------

Handling:

Promptly remove dusty clothing or clothing which is wet with cement fluids and launder before reuse. Wash thoroughly after exposure to dust or wet cement mixtures or fluids.

Storage:

Keep portland cement dry until used. Normal temperatures and pressures do not affect the material.

Portland Cements (Types I, II, III, IV, V)

SECTION 8	EXPOSURE CONTROL / PERSONAL PROTECTION
------------------	---

PERSONAL PROTECTION

Respiratory:

Avoid actions that cause dust to become airborne. Use local and general ventilation to control exposures below applicable exposure limits.

Use NIOSH/MSHA – approved (under 30 CFR 11) or NIOSH – approved (under 42 CFR 84) respirators in poorly ventilated areas, if an applicable exposure limit is exceeded, or when dust causes discomfort or irritation. (Advisory: Respirators and filters purchased after July 10, 1998 must be certified under 42 CFR 84.)

Eye/Face:

Where potentially subject to splashes or puffs of cement, wear safety glasses with side shields or goggles. In extremely dusty environments and unpredictable environments, wear unvented or indirectly vented goggles to avoid eye irritation or injury. Contact lenses should not be worn when working with portland cement or fresh cement products.

Skin:

Prevention is essential to avoiding potentially severe skin injury. Avoid contact with unhardened portland cement. If contact occurs, promptly wash affected area with soap and water. Where prolonged exposure to unhardened portland cement products might occur, wear impervious clothing and gloves to eliminate skin contact. Where required, wear sturdy boots that are impervious to water to eliminate foot and ankle exposure.

Do not rely on barrier creams; barrier creams should not be used in place of gloves.

Periodically wash areas contacted by dry portland cement or by wet cement or concrete fluids with a pH neutral soap. Wash again at the end of the work. If clothing becomes saturated with wet concrete, it should be removed and replaced with clean dry clothing.

Ventilation:

Use local exhaust or general dilution ventilation to control exposure within applicable limits.

Portland Cements (Types I, II, III, IV, V)

SECTION 9	PHYSICAL AND CHEMICAL PROPERTIES
------------------	---

Appearance:

Gray powder

Odor:

No distinct odor

Physical State:

Solid powder

Specific Gravity (H₂O = 1.0):

3.15

Vapor Density:

Not applicable

Vapor Pressure

Not applicable

Evaporation Rate:

Not applicable

Boiling Point:

Not applicable (i.e., >1000C)

Melting Point:

Not applicable

Solubility in Water:

Slightly soluble (0.1 to 1.0%)

SECTION 10	STABILITY AND REACTIVITY
-------------------	---------------------------------

Stability:

Stable

Incompatibility:

Wet portland cement is alkaline. As such it is incompatible with acids, ammonium salts and phosphorus.

Hazardous Polymerization:

Will not occur

Hazardous Decomposition:

Will not spontaneously occur. Adding water produces (caustic) calcium hydroxide.

Conditions to Avoid:

Unintentional contact with water.

SECTION 11	TOXICOLOGICAL INFORMATION
-------------------	----------------------------------

For a description of available, more detailed toxicological information, contact the supplier or manufacturer.

Portland Cements (Types I, II, III, IV, V)

SECTION 12	ECOLOGICAL INFORMATION
-------------------	-------------------------------

Ecotoxicity:

No recognized unusual toxicity to plants or animals.

Relevant Physical and Chemical Properties:

(See Sections 9 and 10)

SECTION 13	DISPOSAL CONSIDERATIONS
-------------------	--------------------------------

Dispose of waste material according to local, state and federal regulations. (Since portland cement is stable, uncontaminated material may be saved for future use.

Dispose of bags in an approved landfill or incinerator.

SECTION 14	TRANSPORTATION DATA
-------------------	----------------------------

Materials Description/Proper Shipping Name:

Portland cement is not hazardous under U.S. Department of Transportation (DOT) regulations.

Hazard Class:

Not applicable

Identification Number:

Not applicable

Required Label Text:

Not applicable

Hazardous Substances/Reportable Quantities (RQ):

Not applicable

SECTION 15	OTHER REGULATORY INFORMATION
-------------------	-------------------------------------

Status under USDOL – OSHA Hazard Communications Rules, 29 CFR 1910.1200

Portland cement is considered a “hazardous chemical” under this regulation, and should be part of any hazard communication program.

Status under CERCLA/Superfund, 40 CFR 117 and 302

Not listed

Hazard Category under SARA (Title III), Sections 311 and 312

Portland cement qualifies as a “hazardous substance” with delayed health effects.

Portland Cements (Types I, II, III, IV, V)

Status under SARA (Title III), Section 313

Not subject to reporting requirements under Section 313 and all potentially covered constituents are present in de minimus concentrations.

Status under TSCA (as of May 1997)

Some substances in portland cement are on the TSCA inventory list.

Status under the Federal Hazardous Substances Act

Portland cement is a “hazardous substance” subject to statutes promulgated under the subject act.

Status under California Proposition 65

This product contains up to 0.05 percent of chemicals (trace elements) known to the State of California to cause cancer, birth defects or other reproductive harm. California law requires the manufacturer to give the above warning in the absence of definitive testing to prove that the defined risks do not exist.

SECTION 16	OTHER INFORMATION
-------------------	--------------------------

Prepared by:

Phoenix Cement Company

Approved by:

Phoenix Cement Company

Approval Date or Revision Date:

February 03, 2010

Date of Previous MSDS:

2005

Other Important Information

Portland cement should only be used by knowledgeable persons. A key to using the product safely requires the user to recognize that portland cement chemically reacts with water, and that some of the intermediate products of this reaction (that is, those present while a portland cement product is “setting”) pose a far more severe hazard than does portland cement itself.

Portland Cements (Types I, II, III, IV, V)

DISCLAIMER:

While the information provided in this material safety data sheet is believed to provide a useful summary of the hazards of Portland cement (types I, II, III, IV, V) as it is commonly used, the sheet cannot anticipate and provide all of the information that might be needed in every situation. Inexperienced product users should obtain proper training before using this product.

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THERE OF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY Phoenix Cement Company, except that the product shall conform to contracted specifications. The information provided herein was believed by Phoenix Cement Company, to be accurate at the time of preparation or prepared from sources believed to be reliable. It is the responsibility of the user to investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence, or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

In particular, the data furnished in this sheet does not address hazards that may be posed by other materials mixed with Portland cement to produce Portland cement products. Users should review other relevant material safety data sheets before working with this portland cement or working on Portland cement products, for example, Portland cement concrete.